



Universal Stacker Conveyor

DESCRIPTION

The Red Rhino SP30 is a site mobile 30ft folding stacker.

Hydraulic controls operate the belt on/off, height discharge range and the folding end section of the conveyor for ease of transport.

A single rear axle, front towing function and weighing 1700kgs makes it easily manoeuvrable on site.

The conveyor has a 9 metres long x 600mm wide belt, a large capacity feed boot to cater for loading shovel, excavator or crusher run loading. This enables it to link up with the Red Rhino Crusher and Screener range of equipment. The stacker conveyor is versatile and can be powered by any other auxiliary supply (20 litres/per min) from other site equipment.

OPTIONS

Self-contained power pack
Kubota OC Series diesel engine
7.0KW EPA Tier 4
12 Volt electric start
Hydraulic function control valve
Oil reservoir complete with oil cooler
Choice of chevron or standard flat conveyor belt
Choice of feed boot capacity

STANDARD FEATURES

- 30ft Conveyor length
- 600mm wide chevron belt
- Folding conveyor end section for ease of transport
- Hydraulically adjustable stockpile height
- Single Axle 200/60 14.5 Agri wheels
- Large capacity feed boot

DIMENSIONS

- Towable length 6856mm
- Raised Stockpile height 3758mm
- Lowest Stockpile height 2760mm
- Width 1940mm
- Weight 1700kg

